



PF53 CONVEYORS

Intended use description



► Features & Benefits

- » **Modular single connection** which is single color-coded, watertight, and ensures the correct connection to the control panel
- » **Clear, hand removable side rails** and open side frame for easy cleaning
- » **Sensors disable conveyors** when side rails are removed
- » **Stainless steel construction** to operate wet or dry
- » **Tooless flip-up tail** relieves belt tension quickly
- » **Sealed stainless steel ball bearings** with covers ensure long life and protection from contaminants
- » **Low profile** with adjustable mounts allows clearance under the conveyor and precise transfers
- » **V-Guided Belt** provides stable guide for belt position after maintenance or cleaning
- » **Precise tension adjustment** is hidden during normal operation allowing for precise tuning for quiet operation
- » **Direct drive gearmotor** saves space and has fewer moving parts than a coupled or underslung design

► Specifications

- » **Brushless DC Gearmotor:** 200 watt IP66 protected CE marked
- » **Full speed rang:** 0.04 to 2 meters/sec [5 – 396 FPM]
- » **70 dBA at 600mm** sound level in free field environment
- » **Set to run drive-pushing**
- » **Weight:** XXX lbs
- » **NSF Certified**

► Part Number

P	F	5	3	C	-	2	5	0	-	3	0	0	0	-	U	V	K	-	C	O	S
Model					Width			Overall			Belt			Application							
Specification					Length			Material			Identifier										
Number					in mm																

► Drawing

